

Express Mail No. EL636003535US

PATENT APPLICATION OF  
SIMON H. CORSTON-OLIVER  
ENTITLED  
LINGUISTICALLY INTELLIGENT TEXT COMPRESSION

Docket No. M61.12-0682

-1-

## LINGUISTICALLY INTELLIGENT TEXT COMPRESSION

### BACKGROUND OF THE INVENTION

The present invention deals with messaging  
5 on devices with limited display space. More  
specifically, the present invention deals with  
compressing text, in a linguistically intelligent  
manner, such that it can be more easily displayed on  
small screens.

10 Messaging is widely available on current  
computer systems. Messages can be sent through voice  
mail, electronic mail (email), paging, and from other  
sources or means. Further, the messages from a  
variety of sources can be integrated and forwarded to  
15 a single device. For example, a user who is  
currently receiving messages at a computer or  
computer network through voice mail and electronic  
mail may forward those messages to a cellular phone  
equipped to receive such messages. However, the  
20 screen of a cellular phone has quite limited display  
space. This can present significant problems when  
trying to display messages.

For example, even very short electronic  
mail messages, or transcribed voice mail messages,  
25 can present text which is too voluminous to be viewed  
on a single screen of a cellular phone. This often  
requires the user to either decipher an entire  
message from the first few words of the message  
(since that is all that can be displayed), or to

scroll down through many lines of text in order to read the entire message. Both approaches are cumbersome and can lead to errors.

While text compression has conventionally  
5 been used in many different contexts, the purpose of such compression has primarily been to enable efficient data storage of text. Such compression techniques are completely inapplicable to contexts in which the compressed text must be deciphered by  
10 humans.

#### SUMMARY OF THE INVENTION

A text processor processes text in a message. The text processor generates a plurality of  
15 compressed forms of components of the message. The processor performs a linguistic analysis on the body of text to obtain a linguistic output indicative of linguistic components of the body of text. The processor then generates the plurality of compressed  
20 forms that can be used to compress the body of text. The plurality of compressed forms are generated based on the linguistic output. The invention can be implemented as a method of generating the compressed forms and as an apparatus.

25 Another aspect of the invention includes a data structure generated based on the linguistic analysis of the text. The data structure includes a plurality of fields that contain attributes indicative of the plurality of compressed  
30 forms of portions of the body of text. The data

structure can also include a compression type field indicative of a type of compression used to generate at least one of the attributes contained in the fields of the data structure.

5

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an embodiment in which the present invention may be used.

FIG. 2 is a block diagram of a message handler for performing linguistic analysis in accordance with one embodiment of the present invention.

FIG. 3 is a diagram of a portion of a syntax parse tree for an exemplary sentence.

FIG. 4 is a flow diagram of the overall operation of the system shown in FIG. 2.

FIGS. 5A and 5B are more detailed flow diagrams illustrating the operation of the system shown in FIG. 2 in generating compression options for terminal nodes (or words and punctuation) in a syntactic analysis.

#### DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

FIG. 1 illustrates an example of a suitable computing system environment 100 on which the invention may be implemented. The computing system environment 100 is only one example of a suitable computing environment and is not intended to suggest any limitation as to the scope of use or functionality of the invention. Neither should the

computing environment 100 be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the exemplary operating environment 100.

5           The invention is operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well known computing systems, environments, and/or configurations that may be suitable for use with the  
10 invention include, but are not limited to, personal computers, server computers, hand-held or laptop devices, multiprocessor systems, microprocessor-based systems, set top boxes, programmable consumer electronics, network PCs, minicomputers, mainframe  
15 computers, distributed computing environments that include any of the above systems or devices, and the like.

          The invention may be described in the general context of computer-executable instructions, such as program modules, being executed by a  
20 computer. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. The  
25 invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both

local and remote computer storage media including memory storage devices.

With reference to FIG. 1, an exemplary system for implementing the invention includes a general purpose computing device in the form of a computer 110. Components of computer 110 may include, but are not limited to, a processing unit 120, a system memory 130, and a system bus 121 that couples various system components including the system memory to the processing unit 120. The system bus 121 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. By way of example, and not limitation, such architectures include Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA) bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnect (PCI) bus also known as Mezzanine bus.

Computer 110 typically includes a variety of computer readable media. Computer readable media can be any available media that can be accessed by computer 110 and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media includes both volatile and nonvolatile, removable and non-removable media implemented in any method or

technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, 5 EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to 10 store the desired information and which can be accessed by computer 100. Communication media typically embodies computer readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier WAV or other 15 transport mechanism and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, 20 and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, FR, infrared and other wireless media. Combinations of any of the above should also be included within the 25 scope of computer readable media.

The system memory 130 includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) 131 and random access memory (RAM) 132. A basic 30 input/output system 133 (BIOS), containing the basic

5 routines that help to transfer information between elements within computer 110, such as during start-up, is typically stored in ROM 131. RAM 132 typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit 120. By way of example, and not limitation, FIG. 1 illustrates operating system 134, application programs 135, other program modules 136, and program data 137.

10 The computer 110 may also include other removable/non-removable volatile/nonvolatile computer storage media. By way of example only, FIG. 1 illustrates a hard disk drive 141 that reads from or writes to non-removable, nonvolatile magnetic media, a magnetic disk drive 151 that reads from or writes to a removable, nonvolatile magnetic disk 152, and an optical disk drive 155 that reads from or writes to a removable, nonvolatile optical disk 156 such as a CD ROM or other optical media. Other removable/non-removable, volatile/nonvolatile computer storage media that can be used in the exemplary operating environment include, but are not limited to, magnetic tape cassettes, flash memory cards, digital versatile disks, digital video tape, solid state RAM, solid state ROM, and the like. The hard disk drive 141 is typically connected to the system bus 121 through a non-removable memory interface such as interface 140, and magnetic disk drive 151 and optical disk drive 155 are typically connected to the system bus 121 by a removable memory interface, such as interface 150.

15  
20  
25  
30



The drives and their associated computer storage media discussed above and illustrated in FIG. 1, provide storage of computer readable instructions, data structures, program modules and other data for the computer 110. In FIG. 1, for example, hard disk drive 141 is illustrated as storing operating system 144, application programs 145, other program modules 146, and program data 147. Note that these components can either be the same as or different from operating system 134, application programs 135, other program modules 136, and program data 137. Operating system 144, application programs 145, other program modules 146, and program data 147 are given different numbers here to illustrate that, at a minimum, they are different copies.

A user may enter commands and information into the computer 110 through input devices such as a keyboard 162, a microphone 163, and a pointing device 161, such as a mouse, trackball or touch pad. Other input devices (not shown) may include a joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit 120 through a user input interface 160 that is coupled to the system bus, but may be connected by other interface and bus structures, such as a parallel port, game port or a universal serial bus (USB). A monitor 191 or other type of display device is also connected to the system bus 121 via an interface, such as a video interface 190. In addition to the monitor, computers

may also include other peripheral output devices such as speakers 197 and printer 196, which may be connected through an output peripheral interface 190.

The computer 110 may operate in a networked  
5 environment using logical connections to one or more remote computers, such as a remote computer 180. The remote computer 180 may be a personal computer, a hand-held device, a server, a router, a network PC, a peer device or other common network node, and  
10 typically includes many or all of the elements described above relative to the computer 110. The logical connections depicted in FIG. 1 include a local area network (LAN) 171 and a wide area network (WAN) 173, but may also include other networks. Such  
15 networking environments are commonplace in offices, enterprise-wide computer networks, intranets and the Internet.

When used in a LAN networking environment, the computer 110 is connected to the LAN 171 through  
20 a network interface or adapter 170. When used in a WAN networking environment, the computer 110 typically includes a modem 172 or other means for establishing communications over the WAN 173, such as the Internet. The modem 172, which may be internal  
25 or external, may be connected to the system bus 121 via the user input interface 160, or other appropriate mechanism. In a networked environment, program modules depicted relative to the computer 110, or portions thereof, may be stored in the remote  
30 memory storage device. By way of example, and not

limitation, FIG. 1 illustrates remote application programs 185 as residing on remote computer 180. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be used.

It should be noted that the present invention can be carried out on a computer system such as that described with respect to FIG. 1. However, the present invention can be carried out on a server, a computer devoted to message handling, or on a distributed system in which different portions of the present invention are carried out on different parts of the distributed computing system.

FIG. 2 is a block diagram of one illustrative embodiment of a number of components that can be used to implement the present invention. FIG. 2 includes a message handler 200 a compressor 202 and a target device 204. Message handler 200 illustratively includes a message parser 204, linguistic analyzer 206 and text compression component 208. In one illustrative embodiment, target device 204 is a cellular phone or other small screen device which is connected to compressor 202 through link 210. Link 210 can be a global computer network that may or may not include radio transmission portions, or any other suitable link for transmitting messages to target device 204.

Message handler 200 illustratively receives message 212. Message 212 can be from one of a

variety of sources, including a paging system, electronic mail, voice mail, etc. Message 212 thus illustratively includes a variety of parts including a header, a body of text, and, in the case of email, previous messages in the email thread. Parser 204  
5 parses message 212 into its various parts. The operation of parser 204 is irrelevant to the present invention. All that is relevant is that a message body 214, or other textual body to be compressed, is  
10 identified and provided to analyzer 206. This can be done in any known way and does not form part of the present invention. Therefore, parser 204 will not be described in detail. Suffice it to say that parser 204 may remove header information and possibly  
15 previous mail messages, and provide the message body 214 to linguistic analyzer 206.

Of course, it should be noted that parser 204 may provide any other natural language body of text to analyzer 206, other than message body 214.  
20 For example, the body of text may be a subject header, a task description header, a web page, etc. The present discussion proceeds with respect to message body 214 as but one example of text to be analyzed.

25 Linguistic analyzer 206 illustratively includes a lexical analyzer, a morphological analyzer, and a syntax analyzer. The lexical analyzer receives message body 214 and breaks it into words (or other tokens). This is done in a known  
30 manner. The morphological analyzer accesses a

morphological data base (such as a dictionary) and obtains a variety of information associated with each word (or token), such as the meaning, the part-of-speech, etc. The syntactic analyzer performs a syntactic analysis of the message body 214 to obtain a syntactic parse tree (or syntactic analysis structure) for each sentence in the message body and outputs that structure as the output of linguistic analyzer 206. This is also done in a known manner and is briefly illustrated with respect to FIG. 3.

Text compression component 208 accesses the linguistic analysis output by linguistic analyzer 206 and generates a plurality of different optional compressions of the components of message body 214. In one illustrative embodiment, text compression component 208 provides five attributes for each word or phrase in message body 214. Generally, each of the attributes represents a more aggressive compression of each word under analysis. In one illustrative embodiment, the data structure output by text compression component 208 includes the following attributes:

ShortType which designates one type of compression rules being applied;

LongForm which is the form of the word as written in message body 214;

ShortForm which is the form of the word after applying the compression rules or techniques identified by the ShortType attribute;

CaseNormalizedForm which capitalizes the first letter in the ShortForm and provides the remaining letters in lower case; and

CompressedForm, which is a compressed form  
5 of the CaseNormalizedForm and subjects the CaseNormalizedForm to additional compression rules in an effort to further compress the word.

In one illustrative embodiment, the data structure including these attributes is output as a  
10 compressed XML output 216 and is provided to the compressor component 202. Compressor component 202 may illustratively choose one of the compressed forms in the compressed output 216 and provide it to target device 204. Compressor component 202 may  
15 illustratively choose the compressed form based on the screen space available on target device 204, or other criteria. It should be noted that compressor component 204 does not form part of the present invention.

20 FIG. 3 is one illustrative embodiment of a sentence which may reside in a message body 214. The sentence reads "You have a meeting with Dr. John Epstein next Tuesday at ten a.m." Of course, message body 214 is provided to the lexical analyzer which  
25 breaks the message body into sentences and into individual words (or tokens). The morphological analyzer then performs a look up of each word (or token) and identifies part-of-speech and other possible information desired for analysis.

Therefore, it can be seen that the words are identified with the parts-of-speech as follows:

you = pronoun  
have = verb  
5 a = article  
meeting = noun  
with = preposition  
Dr. John Epstein = proper noun  
next = adjective  
10 Tuesday = noun  
at = preposition; and  
ten a.m. = noun.

The syntactic analyzer analyzes the sentence and parts-of-speech into a syntax parse tree, in one illustrative embodiment, as indicated in FIG. 3. The terminal nodes (or leaf nodes) in the syntax parse tree represent the words in the sentence, while the non-terminal nodes represent phrases or other upper level syntactic units identifying portions of the sentence. In the syntax parse tree illustrated in FIG. 3, the designation "S" represents a sentence node, while the designation "NP" represents a noun phrase, "VP" represents a verb phrase, and "PP" represents a prepositional phrase. 25 The triangles above "next Tuesday" and "at ten a.m." simply indicate that those phrases can be further analyzed into nodes which have been eliminated for the sake of simplicity. The syntax parse tree indicates that the sentence is formed of a noun phrase, followed by a verb phrase, followed by two 30

other syntactic components which are not specifically analyzed herein.

Text compression component 208  
illustratively compresses the sentence shown in FIG.  
5 3, in a linguistically intelligent manner, such that  
it can be deciphered by a human. In performing such  
compression, a number of problems present themselves.  
For example, it may be intuitive to delete all of  
certain types of words in the text. For instance, it  
10 may be intuitive to delete all articles in the text.  
However, while this may work in English, it does not  
work in other languages. In fact, it does not even  
work in all of the Romance languages. Take for  
example, the French phrase Je le lui ai fait manger  
15 which is translated as "I made him eat it." It  
should be noted that the clitic pronoun "le" looks  
exactly like the definite masculine article "le"  
(which is translated as "the"). Therefore, if all  
"articles" or words "the" and their equivalents in  
20 the different languages were removed, this would  
drastically change the meaning of some phrases in  
different languages.

Similarly, it may seem intuitively  
reasonable to remove all spaces in the text.  
25 However, where electronic mail aliases or uniform  
resource locators (URLs) are provided in the message,  
removing the spaces would make it very difficult to  
tell where the email aliases or URL reside within the  
text. Many such symbol sensitive text fragments are  
30 used in messages today. If case or symbols are



changed in the fragment, the entire fragment irretrievably loses its meaning. Take, for example, the phrase "Visit <http://microsoft.com> for information". If this were reduced to  
5 "visithttp://microsoft.comforinfo" it is very difficult to determine where the URL ends within the text fragment.

Therefore, the present invention does not take such an unintelligent and uniform approach.  
10 Instead, the present invention bases its compression on the linguistic analysis performed by analyzer 206.

FIG. 4 is a flow diagram which illustrates in a bit greater detail the operation of message handler 200. First, message handler 200 receives  
15 message 212. This is indicated by block 218. Parser 204 locates the message body in message 212 and passes message body 214 to analyzer 206. This is indicated by block 220. Analyzer 226 breaks the message 214 into sentences. This is indicated by  
20 block 222. The lexical analyzer component of analyzer 206 then performs a lexical analysis of the text body to break the sentences into tokens such as words, numbers and punctuation symbols. Tokens can also consist of more than a single word, such as  
25 multi-word expressions like "along with" or "by means of". This is indicated by block 224. The morphological analyzer in linguistic analyzer 206 then performs its morphological analysis and thus locates parts-of-speech, and other relevant  
30 information corresponding to each token. This is

indicated by block 226. The syntactic analyzer then performs a syntactic analysis and provides, in one illustrative embodiment, a syntax parse tree. This is indicated by block 228.

5           Text compression component 208 then iteratively examines each of the nodes in the analysis provided by analyzer 206 to determine whether potential compression options are available. This is indicated by block 230. Once the nodes in  
10 the analysis have been examined, and the various compression options have been identified, the compression options are output, as, for example, an XML output 216. This is indicated by block 232. Compressor 202 then simply chooses one of the options  
15 for each word (or token) and provides the message in compressed form to target device 204.

FIGS. 5A and 5B illustrate in better detail the operation of text compression component 208 in generating the potential compression options for the  
20 analyzed portions of message body 214. FIGS. 5A and 5B specifically illustrate the operation of text compression component 208 in generating possible compression options for terminal nodes (or leaf nodes) in the analysis output by analyzer 206. In  
25 other words, FIGS. 5A and 5B illustrate the treatment of each word (or token) in the text message for potential compression, as opposed to non-terminal nodes which may represent phrases or larger fragments of the message body.

First, the long form of each token is received. Recall that the long form is the form of the token which is written in the text body. This is indicated by block 234 in FIG. 5A. The long form is  
5 saved as an attribute that is output in the data structure provided as the compressed output 216. This is indicated by block 236.

Next, the ShortType attribute is determined and saved. Recall that the ShortType attribute is an  
10 attribute that indicates the specific type of compression rules applied to the long form of the token. This is indicated by block 238. The various ShortType attributes in accordance with one embodiment of the present invention are discussed at  
15 greater length below.

It is then determined whether, using the compression rules identified by the ShortType attribute, the entire node under analysis is to be deleted. For example, some nodes are to be deleted  
20 under all circumstances. Articles (which have a ShortType attribute "Articles") in the English language can always be omitted. Such articles include a, the, those, and these, for example. Greetings have ShortType attribute "Greeting" and are  
25 also specially handled in block 240. Greetings (such as Dear Bob, Hi, and Hi BOB) can all be deleted. Determining whether the node is to be deleted under all circumstances is indicated by block 240. If so, then as indicated in block 238, the ShortType  
30 attribute is set to "Articles" (or whatever is

appropriate) and the ShortForm, the CaseNormalizedForms, and the CompressedForm attributes are all set to a null value. This is indicated by block 242.

5           If, at block 240, it is determined that the node is not to be deleted, in its entirety, it is determined whether any other special handling for this node is to be undertaken. This is indicated by block 244. Such special handling can take a wide  
10   variety of forms. A number of those forms will now be discussed.

          A group of adjectives (having the ShortType "Adjective") are specially handled. Those include words which begin with "wh", such as which, who and  
15   what. Those adjectives are discussed in greater detail below.

          English articles were discussed above with respect to block 240. English articles can be omitted under all circumstances. However, articles  
20   in other languages may need special handling. For example, German definite articles can be omitted under all circumstances. However, indefinite articles are retained because of ambiguity (since the same form can mean "a" or "one"). Spanish and French  
25   definite articles are deleted, but clitic pronouns with the same spelling are not. Indefinite articles in Spanish and French are retained because of ambiguity (since the same form can mean "a" or "one").

Adverbs have the ShortType attribute "Adverbs" and those that are classified as "wh" words (why, how, when, etc.) are not compressed in any fashion, and are dealt with below. Other adverbs  
5 undergo character reduction (such as vowel deletion, consonant deletion or both) which is also discussed in greater detail below.

Company names have ShortType attribute "Company" and are also specially handled. The  
10 company type is deleted. For example, "Microsoft Corporation" can be converted to simply "Microsoft". The shortened form is subject to character reduction and case normalization as discussed below.

Conjunctions have the ShortType attribute  
15 "Conjs" and are specially handled as well. For example, the English conjunction "and", the French "et" and the German "und" are replaced with the ampersand sign. The Spanish "y/e" is not reduced since it is already one letter. All other  
20 conjunctions are left as is, and are subjected to the later processing steps.

A number of different types of nouns are specially handled as well. Absolute dates and times are designated with the ShortType "Dates" and are  
25 treated in the following way. In all languages, for a month in isolation, the long month name is converted to a short form. Short month names with periods at the end have the period removed. Vowel compression, case normalization, etc. are not  
30 performed on the resulting short form. For example,

in the phrase "lets meet in November" November is reduced to "Nov". Similarly, the phrase "lets meet in Nov.", has the November abbreviation converted to "Nov" (i.e., the trailing period is stripped).

5           In all languages, a month (and year) with no day of the month designated is rendered as a short month name alone. For example, the term "November 2001" where "2001" is the present year, is simply reduced to "Nov".

10           If the date is a month plus a year that is not the current year, it is converted to a numeric month plus a separator plus a numeric year. For example, "Nov 2002" is converted to "11/2002" (for the English and French languages) or "11.2002" (for  
15 other European languages).

            Similarly, in the American English language, single absolute dates are normalized to month/day/year numerical format. Dates in other languages are normalized to their formats (e.g.,  
20 Japanese always uses the year-month-day format). In English and French the forward slash mark is used as the separator while in Spanish and German the period is used as the separator.

            The year is omitted if it is equal to the  
25 year of "today" or if the year plus 2000 is equal to the year of "today". For example, 23 July, 2001 is converted to 7/23. In addition, Monday 23 July is converted to 7/23.

            Similarly, midnight receives special  
30 handling as well. Midnight is also designated by the

ShortType "Dates" and its short form is "12am". The common collocation "12 midnight" also has the short form "12am", a special case to avoid the output "12 12am".

5           Date ranges in the English language are also subject to special handling. For example, the term "December 5th-9th" is converted to "12/5-9". Also, the date range "December 5th - 9th, 2002" is converted to "12/5-9/2002".

10           Offset dates are also treated specially and are given the ShortType "OffsetDate". In the event that a term such as "next Wednesday" is identified in the text, the date on which the message is sent (or authored) is obtained and the offset date "next  
15   Wednesday" is resolved. Therefore, if the message was sent on Friday, December 1st, the reference to "next Wednesday" would be December 6th. The term "next Wednesday" would thus be converted to "12/6".

          The days of the week are given the  
20   ShortType "Days". In all languages, isolated days of the week that cannot be reliably resolved to absolute dates are converted to the short forms of those days. Short day names with periods at the end have the periods stripped therefrom. Vowel compression, case  
25   normalization, etc. are not performed on the resulting short form. For example, in the phrase "lets meet on Monday", the term "Monday" is converted to "Mon".

          Electronic mail aliases and URL's are also  
30   subject to special handling. Electronic mail aliases

and URL's are maintained, intact, without case normalization or removal of vowels. Emails are given the ShortType "Email" and URL's are given the ShortType "URL".

5           Phone numbers are given the ShortType "Phone" and have punctuation removed from the interior thereof. For example, the phone number in the term "call me at (425) 703-7371" is simply converted to "4257037371".

10           States and countries are given the ShortType "Geo" and are replaced with their conventional abbreviations. For example, "Washington" is replaced by "WA", "Alabama" is replaced by "AL", etc.

15           Non-language items are given the ShortType "NotLanguage" and linguistic compression is not performed. Examples of such items include:

          x = x + y;  
          If (x = 1){

20           < Some XML > Content < /Some XML > <Foo/>.

          Spelled out numbers are also subject to special handling and are given the ShortType "Number". Spelled out numbers are replaced with Arabic numerals. For example, the English phrase  
25 "one thousand four hundred twenty-five" is replaced by "1425". Separators are illustratively not used between thousands.

          Denominations of money are also subject to special handling and are provided with the ShortType  
30 "Dollars". The term "K" is substituted for



thousands. The term "M" is substituted for millions and "B" is substituted for billions. For example, \$100,000 is converted \$100K, \$123,000,000 is converted to \$123M, and \$2,000,000,000 is converted  
5 to \$2B. Also, these short forms are not subject to case normalization which will be described below.

Similarly, in one illustrative embodiment, fractions are indicated as well. For example, \$2,250,000,000 is converted to \$2.25B. Also,  
10 numerical amounts which are followed by a currency designator are normalized to the common symbol for the currency along with the number. For example, "one hundred dollars" is converted to "\$100". The term "57 pounds" is converted to "#57". "500 Francs"  
15 is converted to "500Fr", etc.

Proper names are subject to special handling and are given the ShortType "PrprN". In languages other than German, multi-part proper names are condensed down to just the first family name, if  
20 possible. For example, "Dr. Mary Smith" is converted to "Smith".

It should be noted that for Spanish phrasal last names, they are condensed to the first part (e.g., "Cardoso de Campos" is reduced to "Cardoso").  
25 Also, in one illustrative embodiment, vowel removal is not conducted on proper names.

Similarly, proper names are subjected to dictionary lookup for more common given names. For example, the proper name "Patrick" may be replaced by  
30 "Pat". The name "William" may be replaced by "Will",

etc. Further, if a given name and a final initial are provided, this is reduced just to the first name.

In the German language, proper names are more troublesome, because the language capitalizes many words in text fragments. Therefore, proper names are not compressed when they are preceded by determiners in the German language.

Possessives are also specially handled and are given the ShortType "Possessive". In the English language, possessives with the "'s" and "s'" clitics can be rewritten without the apostrophe. For example, the term "John's house" can be written as "Johns house". Similarly, the "dog's tails" can be written as "dogs tails".

A number of prepositions are subject to special handling as well and are given the ShortType "Preps". For example, in the English language, some prepositions are summarized through a look up table. For instance, "through" can be summarized as "thru". The word "at" can be summarized with "@". The terms "to" and "for" can also be summarized as the numbers "2" and "4" in certain circumstances. They are only summarized in this way if they are not adjacent to a numeral or a number spelled out in full that has a possible numeral substitution. For example, in the phrase "I want to leave", the term "to" is replaced by the number "2". However, in the phrase "I have been to two good movies lately" the term "to" is not changed to the number "2" since this would result in

a possible misconstrual that the speaker had been to twenty-two good movies.

Some pronouns are also subject to special handling and are given the ShortType "Pronouns". For  
5 English, the pronoun "you" is replaced "U". All other pronouns stay the same, with no vowel removal. For Spanish, the pronoun "Usted" is replaced "Ud" and "Ustedes" by "Uds". In the German language, the pronouns that include "ein" (plus inflection) are  
10 summarized using the numeral "1".

Punctuation is specially handled and is given the ShortType "Punctuation". Punctuation that is not a sentence separator and does not occur inside an email alias or URL is deleted. Essential  
15 punctuation is given the ShortType "EssentialPunct". For all languages, the following characters are not deleted: ~ : ; ¿ ? ! [] () <> = == " ". In Japanese, the special small circle symbol which is used exclusively as a sentence separator is not deleted  
20 either. The semicolon and period are deleted only if they are not sentence-final punctuation. All other characters are marked as NonessentialPunctuation (described below).

However, in one embodiment, sequences of  
25 final punctuation are reduced to the first character. Therefore, a phrase such as "Are these things removed?!?" simply has its final punctuation reduced to "?".

Also, for all languages, punctuation that occurs between items which, under other compression rules, may be rendered as digits, are retained. For example, in the phrase "I bought 3 in 1976 and in  
5 1977, 100" the comma after 1977 is retained (or optionally a space is retained) in order to avoid the compression 1977100 and to instead have the compression "1977,100" or "1977 100".

Similarly, in the English language the  
10 inches and foot/feet measurement phrases are converted into " or ' as appropriate.

Other, non-essential punctuation marks are subject to special handling and are given the ShortType "NonessentialPunct". Punctuation inside  
15 factoids (such as email addresses, URL's, numeric ranges, etc.) is left intact. Punctuation not inside such factoids can be deleted except for EssentialPunct and punctuation that occurs as a conjunction (e.g., semi-colons to separate clauses).

20 A number of verbs are also subject to special handling and are given the ShortType "Verbs". Such verbs are subject of dictionary lookups. For example, the word "are" can be replaced by the letter "R", and the word "be" can be replaced by "B".  
25 Otherwise, verbs are simply subjected to character reduction and case normalization as described below.

Two other forms of special handling are performed as well. One is given the ShortType "WordSubstitution" which involves substituting words,  
30 and the other is the handling of the "wh" words

discussed above. A more detailed discussion of those types of special handling is given later in the description.

Discussion now proceeds again with respect  
5 to FIGS. 5A and 5B. If none of these special handling cases are to be undertaken at block 244 in FIG. 5A, then the ShortForm attribute associated with the word under analysis is simply set to the LongForm attribute (which, is the form of the word written in  
10 the text). This is indicated by block 246.

However, if, at block 244, it is determined that special handling is to be done, it is next determined whether the special handling is word substitution. Word substitution is often simply  
15 performed based on a dictionary lookup. Word substitution can be performed, for example, to obtain an acronym for another word or phrase. For instance, in the English language the phrase "as soon as possible" can be substituted with "ASAP".

20 If the special handling is word substitution, then the necessary word substitution is performed for the word in the text in order to obtain the ShortForm attribute. This is indicated by block 250. If word substitution is successful, then the  
25 CaseNormalizedForm (CNF) attribute and the CompressedForm (Comp) attribute are both set to the same form as now found in the ShortForm attribute. This removes the word from further processing such as character reduction and case normalization. This is  
30 indicated by block 252. Therefore, the word

substitution process can be used to avoid other troublesome situations as well. For example, in German the pronoun "sich" can be required (by word substitution) to remain "sich" in order to avoid  
5 later vowel deletion which would result in a common abbreviation for an obscenity. Determining whether the special handling is word substitution is indicated by block 248.

If, at block 248, it is determined that the  
10 particular type of special handling to be undertaken is not word substitution, then it is determined at block 254 whether the special handling to be undertaken is that associated with the "wh" words mentioned above. If so, recall that the "wh" words  
15 are not to be reduced. In that case, all remaining attributes (ShortForm, CaseNormalizedForm, and CompressedForm) are set to the LongForm. This is indicated by block 256.

If, at block 254, it is determined that the  
20 special handling to be undertaken is not that associated with the "wh" words, then it must be one of the other special handling operations discussed above. In that case, the particular special handling step is performed to obtain the ShortForm attribute  
25 and the ShortForm attribute is saved. This is indicated by block 258.

Once the special handling has been performed and the ShortForm attribute has been obtained, the ShortForm attribute is submitted for  
30 space removal. It is first determined whether space

removal is to be done. This is indicated by block 260. If so, then the short form is submitted to a space removal algorithm such as that set out in the following pseudocode.

5

Classify each token as

<EssentialPunct>: assume these need no delineation, and can serve to delineate all tokens

10 <CaseDelineable>: includes all normal words/phrases etc where we can normalize the case

<Number>: numbers (note that these include tokens like "two" that have been converted to "2")

<SpaceDelineable>: tokens that must have a space around them - like url's and email addresses

15

One embodiment of the algorithm:

// start off with the short form sans leading spaces

Result = RemoveLeadingSpaces(<short form>)

// only do this if the token is not NULL

20

if (Result) {

    FrontSpaceNeeded = FALSE;

    // switch on type of current token

    switch <curtype> {

        case <EssentialPunct>:

25

            // should be all done. No delineation required

            break;

        case <CaseDelineable>:

            // put in a space if prev type was space delineable

            if (prevtype == <SpaceDelineable>) FrontSpaceNeeded = TRUE;

30

            break;

        case <Number>:

            // put in a space if prev type is number or space delineable

            if (prevtype == <SpaceDelineable> || prevtype == <Number>

PreviousToken ends in a digit) FrontSpaceNeeded = TRUE;

35

            break;

        case <SpaceDelineable>:

            // put in a space unless previous token was essential punctuation

            if (prevtype != <EssentialPunct> && !IsFirstTokenInSentence)

FrontSpaceNeeded = TRUE;

40

            break;

    }

    // set prevtype to current type

    prevtype = curtype;

    if (FrontSpaceNeeded) Result = AddLeadingSpace(<Result>)

45

}

The pseudocode indicates that spaces will not be removed preceding URLs, email addresses, etc., nor will they be removed following those items. However, in other cases, where delineation can be  
5 made, spaces will be removed from the ShortForm attribute. This is indicated by block 262.

Next, it is determined whether case normalization is to be performed. This is indicated by block 264. It will be appreciated, for example,  
10 that case normalization may not be desired in URLs and emails and other such items that are case sensitive. If that is the case, then the CaseNormalizedForm attribute is set to the ShortForm attribute as indicated by block 266. However, if  
15 case normalization is to be performed, then the first letter in each word in the ShortForm attribute (recall that the token can be composed of multiple words) is capitalized, and that is saved as the CaseNormalizedForm attribute. This is indicated by  
20 block 268.

It is next determined whether further compression is to be performed. This is indicated by block 270. For example, in a number of the special handling cases mentioned above, vowel removal is not  
25 to be performed (such as in pronouns in the English language, the "wh" words, proper names or in the ShortForm of days such as Mon, Tues, etc.). Similarly, vowels or consonants are not to be removed from acronyms, email addresses, URLs, etc.



If further compression is not to be performed, then the CompressedForm attribute is set to the CaseNormalizedForm attribute as indicated in block 272. However, if further compression is to be  
5 preformed, then the CaseNormalizedForm is submitted for character reduction (such as the removal of vowels and consonants).

For the present discussion, the term "medial vowels" will mean a single vowel or a  
10 sequence of vowels that is not either at the beginning or at the end of a word. In the English language, all medial vowels are removed.

15

For removing letters in German, consonant  
20 cluster simplification rules are first applied. For example, the consonant cluster "sch" is simplified to "sh" except in the diminutive suffix -schen. Also, the consonant cluster "ck" is simplified to "k".

Next, the word-final sequence-ein is  
25 replaced with the homophonous -1. Some words in German end in -ein, but it is not homophonous with the number one. Some examples of such words are the following::

30 Codein, Coffein, Casein, Fluoreszein, Hussein, Kaffein, Kasein, Kleberprotein, Kodein, Lutein, Movein, Nuklein, Nuclein, Olein,

5           It should also be noted that if the following word is a number, date, time, etc. (such as anything which may start with a digit), then the "ein" substitution is not performed.

æàáâäëèéêëíîïïœóôõöùûüAAÀÂÃÄÉÊËÈÍÎÏŒÔÕÖÙÛÜ

For English, German, French and Spanish,  
30 consonants include:

qwrtypsdfghjklzxcçvbnñmQWRTYPSDFGHJKLZXCÇVBNÑMß

although additional consonant symbols may be added for other languages.

5           Once character reduction (such as vowel and consonant removal) is performed, as indicated by block 274, the CompressedForm attribute is obtained and saved. This is indicated by block 276. Finally, all five attributes can be output as potential  
10 compression options. This is indicated by block 278.

          It should also be noted that during traversal of the syntax parse tree, compression can be performed on a non-terminal node level as well. In one embodiment, entire phrases are deleted based  
15 on the syntactic analysis. For example, consider the sentence "While I was stuck on the freeway, I remembered to ask you to send me the contact information for Dr. Mary Smith". In this example, the entire sentence initial subordinate clause can be  
20 deleted. In other words, the syntactic analysis indicates that it is subordinate and the subordinating conjunction "while" indicates that this is a temporal adverbial clause. Therefore, this entire phrase can simply be deleted to obtain the  
25 sentence "I remembered to ask you to send me the contact information for Dr. Mary Smith." The patent application Serial No.\_09/220,836, entitled SYSTEM FOR IMPROVING THE PERFORMANCE OF INFORMATION IDENTIFYING CLAUSES HAVING PERDETERMINED  
30 CHARACTERISTICS, filed on December 24, 1998, provides

additional information regarding the identification of subordinate clauses and whether those clauses contain relatively important material.

Another example of compressing at the non-terminal node level is with respect to speech act verbs. Speech act verbs are a subclass of what linguists refer to as "complement taking predicates." In the English language, an ambiguity is illustrated in the following sentence:

10 "John said that he was arriving next Wednesday."

In one reading, the word "he" is co-referential with "John". In another reading, "he" could be someone else. Some elements of this sentence can be deleted without making the output any or more less ambiguous than the input, as follows:

If the subject of the matrix clause speech act verb (in this case "John" the subject of "said") is possibly co-referential with a pronominal subject of the subordinate clause (he), and this can be determined either by noting that they are both masculine, as we know from a morphology lookup, or by using more sophisticated semantic analysis to determine co-reference, then the pronoun in the subordinate clause can be deleted. Note that the subordinating conjunction "that" can also be deleted, to yield:

"John said was arriving next Wednesday".

It should be noted that care must be taken to only delete the subject of the subordinate clause

when it is a pronoun, and possibly co-referential with the subject of the main clause. For example, it should not be deleted in the following case:

John said that she was arriving...

5 John said that Bill was arriving...

John said that they were arriving...

At this point, following through with the example of the sentence illustrated in FIG. 3 may be helpful. As stated earlier, each node in the analysis is iteratively examined to determine whether  
10 compression can be accomplished. Therefore, the sentence node (S) is first examined. No compression can be done at this point, so processing proceeds deeper in the analysis and the noun phrase node 300  
15 is examined. No compression can be performed at that level so processing continues deeper to the pronoun node 302. It is seen that the pronoun is "you". Therefore, under the special handling provisions, this can be converted the term "U". This results in  
20 the following attributes:

ShortType = Pronouns

LongForm = You

ShortForm = U

CNF = U

25 Comp. = U

Next processing continues with respect to verb phrase node 304. It is seen that no compression can be performed at this level so the verb node 306 is examined. The term "have" is simply passed  
30 through the flow chart illustrated in FIGS. 5A and 5B

and subjected to case normalization and vowel removal to obtain the term "Hve". This results in the attributes as follows (wherein the underscore represents a leading space):

```
5      ShortType = VerbsDefault
      LongForm = _have
      ShortForm = _have
      CNF = Have
      Comp. = Hve
```

```
10     Again, examination of the node 308 is done
and it is found that no compression can be done at
this level. Therefore, examination proceeds to node
310 where the article "a" is deleted at block 240 in
FIG. 5A to yield:
```

```
15     ShortType = Articles
      LongForm = _a
      ShortForm = Null
      CNF = Null
      Comp. = Null
```

```
20     The node 312 is then examined, and is
subjected to word substitution to result in the five
attributes as follows:
```

```
      ShortType = WordSubstitution
      LongForm = _meeting
25     ShortForm = Mtg
      CNF =      Mtg
      Comp. =    Mtg
```

```
      The prepositional phrase node 314 is then
examined and it is determined that no compression can
30 be done at that level. Therefore, the preposition
```

node 316 is examined. Processing moves through the flow chart in FIGS. 5A and 5B and case normalization and vowel removal are conducted to yield the five attributes as follows:

```
5           ShortType = PrepsDefault
           LongForm = _with
           ShortForm = _with
           CNF = With
           Comp. = Wth
```

```
10          The proper noun node 318 is then examined.
It is found, at this node, the three words "Dr. John
Epstein" can be compressed using the ShortType PrprN.
This yields the five attributes as follows:
```

```
           ShortType = PrprN
15          LongForm = _Dr._John_Epstein
           ShortForm = _Epstein
           CNF = Epstein
           Comp. = Epstein
```

```
           Next, node 320 is examined and is found
20 that this phrase represents an offset date. This is
analyzed, through the flow diagram illustrated in
FIGS. 5A and 5B to yield the following five
attributes:
```

```
           ShortType = OffsetDate
25          LongForm = _next_Tuesday
           ShortForm = _12/3
           CNF = 12/3
           Comp. = 12/3
```

Next, node 322 is examined and it is determined that no compression can be made at that node. Therefore the preposition node 324 is examined. It is noted, through processing as  
5 indicated in FIGS. 5A and 5B that the term "at" is the subject of a word substitution for "@" this yields the five attributes as follows:

```
ShortType = WordSubstitution
LongForm = _at
10 ShortForm = @
    CNF = @
    Comp. = @
```

Finally, the node 326 is examined and the only compression that is found is to replace the  
15 spelled-out term "ten" with the number "10" to yield the five attributes:

```
ShortType = Numbers
LongForm = _ten_am
ShortForm = _10am
20 CNF = 10am
    Comp. = 10am
```

The compressor 202 is then free to pick and choose among the various compression options illustrated in these data structures to provide a  
25 final output compressed version of the text. This can be done very aggressively, as in the case of the display screen on the target device 204 with a very limited size, or it can be done less aggressively, as in the case of a palm top computer with more display



space, for instance. Therefore, for example, the most aggressive compression is as follows:

UHveMtgWthEpstein12/3@10am

Even with very aggressive compression, this  
5 is a highly readable and decipherable text message, yet is saves a great deal of space over the original set out in FIG. 3.

Thus, it can be seen that the present invention can be used to provide significant  
10 compression, yet the compression is made in a highly linguistically intelligent fashion such that it can be easily deciphered by a human. It also provides a plurality of different compression options for individual words and phrases, which, in most cases,  
15 reflect various degrees of aggressiveness. This is tremendously helpful to the downstream components which eventually must choose the best compression sequence in the target device.

Although the present invention has been  
20 described with reference to particular embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.